

AL101 Leak Protection Device, Indoor Alarm Part No.: AL101-1-2R-FRP Indoor Single Alarm Panel

The Model AL101-1-2R-FRP is an Indoor alarm panel that accepts a switch contact input and provides an audible alarm signal when the external contact is closed. It must be mounted in a non-hazardous location. The white pilot light indicates the 120 VAC power. The TEST push-button is a momentary button that turns on the red light and the horn. The red pilot light provides the visual alarm indication for the alarm contact. The MUTE push-button is a momentary button that mutes the horn for the alarm input. In the event of a power failure the alarm will come back on with the power. The red light remains on until the alarm condition is corrected. The alarm circuit resets automatically. The panel also has 2 relay dry contact outputs. Use Ktech float switches for the alarm input contacts.

Electrical Specifications

- 120 VAC, 60 Hz, 85mA
- Switch input at terminals **3&4**
- Relay Output at terminals **5&6&7, 8&9&10**
 - Contact rating: 10A
- Wire Gauge Range is 20-10AWG
- Buzzer -- 95 dB @ 1 ft.



**LISTED
NONVOLUMETRIC
LEAK DETECTION
DEVICES
4YC9**

CAN/ULC-S675.2-14



**Certified to CSA C22.2 No.205 and Conforms to UL2017
CAUTION: REFER TO INSTRUCTIONS BEFORE OPERATING ALARMS**

